


- Engine & Cooling
- Fuel
- Ignition
- Electrical
- Running gear
- Torque settings
- Capacities
- Notes & Illustrations



Automotive Technical DATA BOOK

Click on one of the buttons above to view data for this car. To return to this screen and make another choice, click anywhere on the data screen.

MENU

HELP

Engine and cooling system 840 Ci (E31) 1996 to 1997

Type	M60 4.4 210kW DOHC 32V	
Capacity (cm ³) / number of cylinders	4398 / 8	
Compression ratio / pressure	bar	10.0 / ≥10.0
Oil pressure	bar	≥0.5 [4.5]
Oil temperature	°C	80
Valve clearance - inlet	mm	0: Hyd.
Valve clearance - exhaust	mm	0: Hyd.
Firing order	1-5-4-8-6-3-7-2	
No 1 cylinder position	PER	
Thermostat opening temperature	°C	85
Radiator cap pressure	bar	2.0±0.1

Fuel system 840 Ci (E31) 1996 to 1997

Idle speed - manual [auto]	rpm	600±50
Fast idle speed - manual [auto]	rpm	—
CO @ idle speed [3000 rpm] - see page VI	%	≤0.3 N/A
HC @ idle speed [3000 rpm] - see page VI	ppm	≤200
CO ₂ @ idle speed [3000 rpm] - see page VI	%	—
O ₂ @ idle speed [3000 rpm] - see page VI	%	—
Carburettor / fuel injection	Bosch	
Type / ref	M5.2-Motronic	
Main jet / needle	—	
Injection pressure	bar	—
Pump pressure	bar	3.5±0.06
Octane rating	RON	95[U]

Ignition system 840 Ci (E31) 1996 to 1997

Type	Direct electronic	
Ignition coil	Bosch	
Primary resistance	ohms	0.8±0.1
Ballast resistor	ohms	—
Voltage - Tmnl 15(+) to earth	V	—
Distributor	—	
Points gap (air gap)	mm	[0.30 to 0.70]
Dwell angle	° (%)	—
Condenser capacity	µF	—
Rotation	—	
Ignition timing - basic [static V = Vacuum NV = No Vacuum]	° Crankshaft @ rpm	Computer control N/A
Total ignition advance	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Centrifugal check.	° Crankshaft @ rpm	Computer control
	° Crankshaft @ rpm	—
	° Crankshaft @ rpm	—
Vacuum range check	mbar	Computer control
Maximum vacuum advance	° Crankshaft	—
Spark plugs	NGK/Bosch	
Type	BKR6EK / F7LDCR	
Electrode gap	mm	0.70+0.10

Electrical system 840 Ci (E31) 1996 to 1997

Battery	V / CC / RC	12 / 130Ah
Alternator voltage / full load current / engine rpm	14.2 to 14.4 / 140 / 3000	
Starter motor current / voltage - cranking	A / V	—
- locked	A / V	—

Running gear 840 Ci (E31) 1996 to 1997

Brakes -		
Front (min. friction material thickness)	mm	2.0
Rear (min. friction material thickness)	mm	2.0

Tyres		
Saloon	Size	235/50x16
Estate / Van	Size	—
Pressure - front / rear - Saloon	bar	2.5 / 2.5
- Estate / Van	bar	—

Front suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+18'±5']
Camber	-11'±30'. Sport: -25'±30'	
Castor	+8°14'±30'. Sport: +8°53'±30'	
King pin inclination	+12°4'±30'. Sport: +13°4'±30'	

Rear suspension / wheel alignment		
Toe-in (+) / Toe-out (-)	mm [°]	[+18'±6']
Camber	-1°10'±15'. Sport: -1°23'±15'	


Torque wrench settings 840 Ci (E31) 1996 to 1997

Cylinder head - stage 1	Nm	30±2 N
- stage 2	Nm	+ 80±5°
Cylinder head - stage 3	Nm	+ 80±5°
- stage 4	Nm	—
Big-end bearings	Nm	5, 20±1 + 80±5° N
Main bearings	Nm	20 + 70° N
Clutch cover	Nm	25
Flywheel [driveplate]	Nm	105±5 N
Front hubs	Nm	290
Rear hubs	Nm	300
Wheel nuts / bolts	Nm	100±10
Spark plugs	Nm	30 to 33

Capacities 840 Ci (E31) 1996 to 1997

Engine oil & filter	litres	7.5
Gearbox - 4-speed [5-speed]	litres	1.75
Automatic transmission - refill	litres	5.5
Final drive	litres	1.9
Cooling system	litres	12.0
Fuel tank	litres	90

Notes and Illustrations



3982 cm³, M60