



STRIP-DC-ON

- NOTES: (UNLESS OTHERWISE SPECIFIED)
1. ALL RESISTORS IN OHMS, 1/4 W. 5%.
  2. ALL CAPACITORS IN P.F. (1/2).
  3. FOLLOWS DENOTED BY (1/2).
  4. THESE SCHEMATIC SUBJECT TO CHANGE WITHOUT NOTICE.
  5. ABBREVIATIONS: K-1000.
  6. POLY-POLYESTER.

| LAST NUMBER | NOT USED     |
|-------------|--------------|
| R46         | R41, R7, R43 |
| C22         | C2, C3       |
| D28         | D15, D23     |
| S31         |              |
| Q3          |              |
| K42         |              |
| K5          |              |
| S6          |              |
| INI         |              |
| F3          |              |
| CB1         |              |
| NE1         |              |

- ALL MEASURED AT NOM 117 V LINE.
- AC MEASURED NO LOAD WITH RESPECT TO POINT S. SELECT TP WITH LEVEL CONTROL.
  - RESISTORS NO LOAD, WITH RESPECT TO POINT M.
  - AC MEASURES NO LOAD WITH RESPECT TO POINT M.
  - S\* AT 400 V, 200 MA OUTPUT MEASURED WITH RESPECT TO CIRCUIT S (NOT OVERLOAD).
  - S\* AT 400 V, NO LOAD MEASURED WITH RESPECT TO CIRCUIT S (NOT OVERLOAD).
  - S\* OVERLOAD LAMP ON MEASURED WITH RESPECT TO CIRCUIT S (NOT CHASSIS).

